Embelle®




Ember Knob

K200 series

Ember Knob

K200 series

INTERIOR FUNCTIONS · PRIVACY (R), PASSAGE (A) & DUMMY (U)



SPECIFICATIONS

LOCK MEASUREMENTS	
Knob diameter	Ø 2.30"
Knob projection	2.84"
Knob clearance	1.84"
Knob depth	1.00"
Rosette depth	.39"
DOOR PREP	
Backset	Adjustable 2-3/8" & 2-3/4"
Cross bore	2-1/8"
Edge bore	1"
Door thickness	1-3/8" – 1-3/4"
Face plate	1" × 2-1/4" radius
USAGE & FEATURES	
Fasteners	Not concealed
Handing	Non-handed
Area	Interior
Doors	Wooden & metal
CERTIFICATION	
ANSI	Meets or exceeds ANSI A156.2

ROSETTES

Round (D)	Ø 2.56"
Square (Q)	2.57" × 2.57"
Rectangle (G)	3.96" × 2.46"

AVAILABLE FINISHES


Additional finishes available upon request


US19 Dull Black (DB) US26 Bright Chrome (BC) US4 Satin Brass (SB)
US15 Satin Nickel (SN)

HOW TO ORDER

e.g. LCDK20RDB

LC	D	K20	R	DB
PREFIX	ROSETTE D Round · Q Square · G Rectangle	SERIES	FUNCTION R Privacy · A Passage · U Dummy	FINISH DB · BC · SB · SN





Privacy (R)
Bed & Bath

Passage (A)
Hall & Closet

Dummy (U)
Non-Functional

Embelle®

Ember Knob

KEYED FUNCTION · ENTRY (N)

K200 series



SPECIFICATIONS

LOCK MEASUREMENTS	
Knob diameter	Ø 2.24"
Knob projection	2.76"
Knob clearance	1.78"
Knob depth	.98"
Rosette depth	.39"
DOOR PREP	
Backset	Adjustable 2-3/8" & 2-3/4"
Cross bore	2-1/8"
Edge bore	1"
Door thickness	1-3/8" – 1-3/4"
Face plate	1" × 2-1/4" radius
USAGE & FEATURES	
Keyway	KW1 (default) · SC1 available at no cost
Fasteners	Not concealed
Handing	Non-handed
Area	Interior & common area
Doors	Wooden & metal
CERTIFICATION	
ANSI	Meets or exceeds ANSI A156.2

ROSETTES

Round (D)	Ø 2.56"
Square (Q)	2.57" × 2.57"
Rectangle (G)	4.03" × 2.46"

AVAILABLE FINISHES


Additional finishes available upon request


US19 Dull Black (DB) US26 Bright Chrome (BC) US4 Satin Brass (SB)
US15 Satin Nickel (SN)

HOW TO ORDER

e.g. LCDK20NDB

LC	D	K20	N	DB
PREFIX	ROSETTE D Round · Q Square · G Rectangle	SERIES	FUNCTION N Entry	FINISH DB · BC · SB · SN





Entry (N)

Entrance

Embelle®